Applicant: David Arsenault Serial No.: 09/693,840

Filed : October 23, 2000

Page

Replace the paragraph beginning at page 5, line 17 with the following rewritten paragraph:

-- Proxy server 120 generally includes a cache of previously downloaded network resources (e.g., web pages). When a browser request from client computer 110 is received by proxy server 120, the proxy server filters each browser request against the cache of previously downloaded network resources. If a match exists between the browser request and a cached network resource, proxy server 120 is able to generate and return a response to client computer 110 without forwarding the browser request to network 130. Conversely, if the browser request does not match a cached network resource, proxy server 120 uses one of its own IP addresses to request the network resource from destination server 140 over network 130, with proxy server 120 acting as a client on behalf of client computer 110. When the requested network resource is returned to proxy server 120, that network resource is forwarded to client computer 110. In the implementation of fig. 1A, proxy server 120 includes one or more trap lists 120a that are used for comparison against browser requests received from the browser software on client computer 110.--

Replace the paragraph beginning at page 5, line 30 with the following rewritten paragraph:

-- Fig. 1B provides an example of a trap list 120a. This particular trap list 120a shows a list of domain names against which browser requests from client computer 110 are compared and with which browser requests including selected domain names (a "selected browser request") are identified. Trap list 120a also may include other criteria against which browser requests may be compared, such as, for example, uniform resource locators (URLs). Furthermore, as an alternative or complement to trap list(s) 120a, proxy server 120 may include other search and/or filtering criteria or algorithms used to identify selected browser requests. In any event, the proxy server 120 specifies one or more destinations for browser requests discriminated by the trap list 120a or other search and filtering criteria. --